


TOP 44

**3.96(.156)
CENTERS**

**6.35(.250)
PLUNGER TRAVEL**

Dimensions in mm (inches)

TECHNICAL DATAS



Minimum centers:	3.96 mm (.156)
Full travel	6.35 mm (.250)
Rated stroke	4.20 mm (.165)
Probe resistance	< 10 MOhm
Operating temperature	-55°C/ +105°C (-67°F/+221°F)
Current rating	5 AMP

MATERIALS AND FINISHES


Plunger	Copper alloy, gold plated
Barrel	Copper alloy, gold plated
Spring	Music wire, gold plated

SPRING FORCE IN GR. (OZ.)

PRELOAD	2/3 TRAVEL
60 (.2.12)	130 (4.59)
80 (2.82)	190 (6.70)
120 (4.23)	300 (10.58)

Additional spring forces available. Please consult factory

RECEPTACLE SPECIFICATIONS



MOUNTING HOLE SIZE

2.72/ 2.77 (.107/.109)



CONNECTIONS

- CRIMP - C
- SOLDER - S
- WIRE WRAP - W

MATERIALS AND FINISHES

BARREL	Copper alloy gold plated
SQUARED POST.	Ph Bronze gold plated

AVAILABLE HEAD STYLES

Head style	Available diametres	Head style	Available diametres	Head style	Available diametres
	1.20(.047) 1.50(.059)				
	1.50(.059)				
				NOTES	
				MATERIALS S - STEEL L - COPPER ALLOY	

HOW TO ORDER

MODEL TOP 44	HEAD C	HEAD DIA 1.20	SPRING FORCE 2/3 TRAVEL 190	TREATMENT G
-----------------	-----------	------------------	-----------------------------------	----------------